

"LEBEN" NEW STEREO POWER AMP. CS-660P

One of Mr.Hyodo's favourite KT66 based power amplifiers is the QUAD II,
(The QUAD II has recently been re-launched due to the demand from audiophiles)

M Hyodo has now decided to design a new power amplifier using the same KT66 tube but incorporating high-end audio grade components, far superior to those used in the original QUAD design.

INTRODUCTION OF LEBEN CS-660P

TWO CHOICES OF OUTPUT TUBES: KT-66 AND OPTIONAL 6CA7(EL34)

By switching two selectors inside of the cabinet, you can use either **KT-66 or 6CA7(EL34)**, a LED indicator at the foot of each tube will change its colour and show you which tube is in use.

You also can use several other tubes of different sound characteristic.(Refer to the Tube List)

STEREO/MONO SELECTOR SWITCH

You can use CS-660P as a monaural power amplifier by changing the selector switch giving an **80W** output power.(40W x 2 when used as a stereo power amp.)

A WIDE RANGE OF SPEAKER APPLICATION

Multi output impedance selector: **4/6/8/16 ohms**.

FLAT AND WIDE FREQUENCY RESPONSE

A wide frequency response **from 10Hz to 100KHz** (-0dB) caters for digital audio formats such as SACD/HDCD.

OTHER FEATURES

- * Twin-triode tube 6CS7 for the first-stage amplification.
- * WBT type speaker terminals.
- * Large capacity choke-coil: **400mA**
- * **Dumper tube 6CJ3** (for Colour TV use) is applied to delay a supply of high voltage(B-Voltage) to output tubes in order to protect output tubes from damage and to increase tube life.
- * All high-end audio grade electrical components(condensers, resistors)
- * Operation indicator lights up when the tubes are warmed up.
- * Wood Side-Panels.

CS-660P SPECIFICATIONS	
TUBE COMPLIMENT	(4) KT-66, (EL34/6CA7 - Option) (4) 6CS7 (1) 6CJ3
OUTPUT POWER (Stereo/Mono Selector Switch)	Stereo 40W x 2 (KT-66) at 1KHz. Monaural 80W X 1 (KT-66) at 1KHz.
FREQUENCY RESPONSE	10Hz - 180KHz. (-3dB)
INPUT SENSITIVITY	1.5V at 40W
INPUT IMPEDANCE	100KΩ
OUTPUT IMPEDANCE	4/6/8/16 Ohms (Selectable)
POWER CONSUMPTION	230W
WEIGHT	17.0kg
DIMENSIONS	415(W) X 480(H) X 320(D) mm
ATTACHMENT	Detachable AC Power Cable x 1